

DA 300



- Terminal for direct connection
- Conductor cross-section: 25 mm² - 300 mm²

ELECTRICAL PROPERTIES

Rated current (of the terminal): 400 A

CONNECTION DATA

Terminal cross-section:

Maximum number of conductors clamping units each	Conductor cross-section min.	Conductor cross-section max.	Conductor cross section	Conductor type	Conductor material
1	25 mm ²	300 mm ²	solid, stranded	round, sector	Cu, Al

Connection type:

Connection type	Connection size
Bolt connection	M 10

Connection type:

Type of cable	Connection type	Connection size
	Bolt connection	M 10

DIMENSIONS

Width: 42 mm
Net weight: 0.191 kg

SALES DATA

Product number: 26001625
EAN: 4012591135890
Pack unit: 1
Customs tariff number: 85371098
ETIM class: DYNAMIC: EC001894 - Distributor assembly terminal blocks
ETIM-4.0: EC001894 - Distributor assembly terminal blocks
ETIM-5.0: EC001894 - Distributor assembly terminal blocks
ETIM-6.0: EC001894 - Distributor assembly terminal blocks
ETIM-7.0: EC001894 - Distributor assembly terminal blocks

NOTE

Before connecting, aluminum conductors must be pre-treated according to the appropriate technical recommendations, see technical information aluminum conductors

TENDER TEXT

Terminal for direct connection DA 300, 300 mm², up to 400 A
Dimensions HxWxD 72 x 42 x 86 mm